

95STS Single Valve Series Commercial Water Filter

Nextsand (95STS NX Filter)

NEXTSAND (95STS NX FILTER) Remove suspended solids, ferric hydroxide (red water iron) or sediment from your well or water system down to 5 microns. Nextsand has proven extremely effective and will provide double the service flow rates of multi-media or sand filters.

Canature WaterGroup™ has dedicated professional engineers with decades of commercial water treatment experience. Over the years, they have built a reputation for designing efficient, high quality commercial water systems.

Our **95STS Single Valve Series** filters provide high quality filtered water. The system is engineered and thoroughly tested to provide years of reliable, trouble-free performance with minimal maintenance.

Operating Parameters

- Operating pressure: 20 - 100 psi
- Operating temperature: 39 - 100° F
- Electrical: Input 120V 60 Hz - Output 12VAC

Materials of Construction

- Control Valve: Plastic PPO (Noryl)
- Resin Tanks: Corrosion resistant fiberglass reinforced polyethylene NSF 44 Certified
- Internal Distribution

Standard Features

- 95 high flow control valve with RWB piston (standard)
- Large display: Fully programmable and easy to set electronic controller
- Inlet/Outlet connection sizes available in 1", 1.25", and 1.5"
- Advanced Diagnostic Information: Easily trouble shoot and access system information displayed in real time
- Optional Auxiliary Contact: activated for regeneration cycle
- Battery Back-up System: In the event of a power outage, the system can continue to meter and monitor water usage for up to 9 hours

For Applications Such As:

- Apartments ● Boiler Treatment ● Cooling Towers ● Hotels ● Schools ● Nursing Homes
Car Wash ● Dairies ● Factories ● Laundromats ● Office Buildings ● Resorts
Restaurants ● RO Pre-treatment ● Office Buildings ● Hospitals



95STS Single Valve Series Commercial Water Filter Specifications

Nextsand Filters

Model	Typical	RO	Max Flow To Drain	Mineral Tank		Installation		
	Service Flow Rate			Diameter	Height	Height	Depth	Width
	USGPM (L/S)	USGPM (L/S)	USGPM (L/S)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)
95STS NX14-1.25"	10 (0.63)	8 (0.50)	14 (0.88)	14 (356)	65 (1,651)	75 (1,905)	20 (508)	20 (508)
95STS NX16-1.25"	14 (0.88)	11 (0.69)	17 (1.07)	16 (406)	65 (1,651)	75 (1,905)	22 (559)	22 (559)
95STS NX18-1.25"	17 (1.071)	13 (0.819)	21 (1.32)	18 (475)	65 (1,651)	75 (1,905)	24 (610)	24 (610)



95STS Single Valve Series



Commercial/Industrial
Engineering Division

TOLL-FREE: 877-288-9888
www.canaturewg-cied.com

Regina, SK • Cambridge, ON • Carmel, IN • Pottstown, PA
Phoenix, AZ • Guadalajara, MX